

# BR-MOD-1-9 Satellite Beacon Receiver Module



- Track L-Band CW Beacon Carrier; BPSK Carrier
- CEPT-Carrier-Edge-Power-Track for DVB Carrier
- For Integration in On-The-Move Applications
- Monitoring & Control (M&C) via Ethernet
- Integrates with Avcom's EVO-GUI
- Comprehensive API for Easy Integration
- Extended Temperature Range
- Low SWaP (Size, Weight, and Power)



RF	TECHNICAL SPECIFICATIONS
INPUT CONNECTOR:	SMA, 50 Ohm
INPUT FREQUENCY RANGE:	930 to 2175MHz
TUNING STEP SIZE:	1kHz
INPUT LEVEL RANGE:	-10 to -100 dBm
MAXIMUM INPUT POWER LEVEL:	- 10 dBm max
DETECTION BANDWIDTH:	10 to 750 kHz
TRACKING BANDWIDTH:	10 to 150 kHz
DETECTED BEACON LEVEL FILTERING:	Low-Pass, User-Select: 0.25 Hz, 0.5 Hz, 1.0 Hz, 2.0 Hz, 3.0 Hz

For ordering information email: [salesrfq@avcomofva.com](mailto:salesrfq@avcomofva.com) or call 804-794-2500

## BR-MOD-1-9; TECHNICAL SPECIFICATIONS Cont.

PARAMETER	PERFORMANCE
SEARCH/TRACK RATE:	User-Selectable: 10 Hz, 25Hz
ACQUISITION TIME:	<1 second typical
ADJUSTABLE DELAY BEFORE LOCK:	0 to 5000 milliseconds
ACQUISITION/TRACKING LEVEL:	Minimum C/No, 39 dB-Hz
BEACON/CARRIER TYPE:	CW, BPSK(No Demod), CEPT(Carrier-Edge-Power-Track) on DVB(No Demod)
<b>M &amp; C</b>	
ETHERNET:	10/100; Magnetics on-board, 4-pin Molex
IP ADDRESS:	DHCP or Static
INCLUDED CONTROL APPLICATION:	Avcom GUI (Windows)
APPLICATION PROGRAMMING INTERFACE (API):	POSIX-compliant 'C' Pre-built Libraries for Windows and Linux x86 Source code available
PROTOCOL:	High-reliability closed-loop with error checking
RECEIVER OUTPUT VIA PHYSICAL OUTPUTS:	Yes
RECEIVER OUTPUT VIA M&C INTERFACE:	Yes
<b>RECEIVER OUTPUTS</b>	
CONNECTOR:	6-pin Molex
ANALOG SIGNAL STRENGTH INDICATOR OUTPUT:	0 to 10 VDC, 25 mA
ANALOG SLOPE:	0.1 to 3.0 Volts/dB
ANALOG SLOPE POLARITY:	Positive or Negative
ANALOG OUTPUT FILTERING:	Low-Pass, 0.5 Hz, fixed
DIGITAL LOCK INDICATOR OUTPUT:	0 - 3.3 VDC
DIGITAL LOCK INDICATOR OUTPUT POLARITY:	Adjustable (H=LOCK or L=LOCK)
<b>POWER</b>	
CONNECTOR:	2-pin Molex
POWER SUPPLY:	15 - 24 VDC; < 3 W
<b>PHYSICAL</b>	
DIMENSIONS:	3 in. x 3.5 in. x 1.057 in.
WEIGHT:	8 oz; 200g
<b>ENVIRONMENTAL</b>	
OPERATING TEMPERATURE:	-40°C to 70°C
STORAGE TEMPERATURE:	-40°C to 85°C
HUMIDITY:	0 to 95%, non-condensing
OPERATING ALTITUDE:	40,000 ft; 12,000 m

For ordering information email: [salesrfq@avcomofva.com](mailto:salesrfq@avcomofva.com) or call 804-794-2500